




Before you start mounting the flashings please check the dimensions above, which show the ready mounted dimensions of the flashing. You have to add the dimensions of the flashing to the dimensions of the solar-panel so you will get the ready mounted dimension of the whole solar-system.


This mounting instruction is valid for corrugated and flat roof tiles (for flat roof-tiles the foreparts are fabricated without lead-apron!!





Before you start mounting of the foreparts must ad an additional roof batten to stabilisize the foreparts. The distance for this additional roof batten please see in the picture above.

















The left panel has to be hooked into the laps of the forepart as showed in the picture above. The panel must be moved until the left edge reaches the marked sign on the forepart.








Now fit the second panel in the middle-forepart (or in the case of only 2 panels in the right forepart). The second panel must be fitted in the same way like the first one.





After you have placed the second panel, fix it with the longer fixation brackets together with the right side of the first panel. See the detailed picture on the right side. If you have only a 2-panel-system you can start fixing the right side of the second panel, in the same way as the left side of the first panel.





























The next step is to mount the upper connection-parts. You just hook them in the upper edge of the panel and put them down until they fit

with the panel-surface and cover the lower connection-part.













The mounting of the back-parts starts with the left one. You have to fit it in the left lateral-part and hook it into the upper edge of the panel. **Do not fix the back-part now.**


The middle back-part (only necessary for more than 2 panels) just has to be hooked in the uper edge of the panel. It has to be placed that it is exactly in the middle between the left and the next-coming right part.

















Fixation with rivets: You have to fix the single parts with rivets on the points shown in the picture. There are only holes in the covering parts so you have to drill that you can place the rivets.

Around the lateral- and the backparts place foam-gascets like in the picture shown.

Only necessary in the case of corrugated roof material!!